

## Fabric Data Sheet

Product: **PC6571000**      Style : PW      Customer Spec:

Description: 152GSM/PW/High Strength 3K, 200 tex & Innegra 940 Den S/1200mm

<b>Warp Fibre</b>	AF	<b>Fibre</b>	Ends/10cm  50 ±2.5
	AF996	High Strength 3K, 200tex	
	AF243	940 Den Innegra S 30tpm S	
		#####	

<b>Weft Fibre</b>	AF	<b>Fibre</b>	Picks/10cm  50 ±2.5
	AF996	High Strength 3K, 200tex	
	AF243	940 Den Innegra S 30tpm S	
		#####	

<b>Leno Yarn</b>	K29/220Dtex Twisted (AF175)
------------------	-----------------------------

Tolerances/Testing/Frequency
------------------------------

<b>Product Quality Plan</b>	<b>C</b>
-----------------------------	----------

Check	Test Method	Nominal	Tolerance.
Mass	001/2/8	152	±8      gsm
Width	003	1000	-0, +10mm
Ends/10cm	004/005	50	
Picks/10cm	004/005	50	±2.5
Picks/Inch	010	12.70	
<b>Check</b>	<b>Test Method</b>	<b>Maximum</b>	
Weft Bow	006	30 mm/mt width	
Warp Bow	007	5 mm/mt length	
Nominal Length (metres)		102	
Construction	012	Verify	
Thickness	011	Verify	

Test Methods details refer to information as set in Sigmatex Quality Manual

Special Instruction :	
-----------------------	--